

12/08/2009



FACTORY FIVE CHALLENGE SERIES



"Gentlemen, start your engines!"

2010 EDITION

THIS BOOK IS AN OFFICIAL PUBLICATION OF THE NATIONAL AUTO SPORT ASSOCIATION. COPYRIGHT ©2008 ALL RIGHTS RESERVED

THE CONTENTS OF THIS BOOK ARE THE SOLE PROPERTY OF THE NATIONAL AUTO SPORT ASSOCIATION. NO PORTION OF THIS BOOK MAY BE REPRODUCED IN ANY MANNER, ELECTRONICALLY TRANSMITTED, POSTED ON THE INTERNET, RECORDED BY ANY MEANS, OR STORED ON ANY MAGNETIC / ELECTROMAGNETIC STORAGE SYSTEM(S) WITHOUT THE EXPRESS WRITTEN CONSENT FROM THE NATIONAL EXECUTIVE DIRECTOR OF THE NATIONAL AUTO SPORT ASSOCIATION.

National Auto Sport Association, Inc.
National Office
P.O. Box 21555
Richmond, CA 94820
<http://www.nasaproring.com>
510-232-NASA
510-412-0549 FAX

TABLE OF CONTENTS

1. INTRODUCTION.....	5
1.1 Intent	5
1.2 Acronyms Defined.....	5
2. ELIGIBLE MODELS.....	5
2.1 Definitions.....	5
2.1.1 Factory Five Racing Kit Car Eligibility.....	5
2.1.2 Ford Mustang ‘Donor’ Car Eligibility.....	5
3. SAFETY.....	5
3.1 Conformance to the NASA <i>Club Codes and Regulations</i> (CCR)	5
3.2 Cage/Rollover Protection	6
3.3 Drive Shaft Safety Loop	6
3.4 Scattershield	6
3.5 Master Switch.....	6
3.6 Fuel Cell	6
3.7 Fuel Cell - Trunk Access	6
3.8 7 Anti-intrusion protection.....	6
3.9 8 Safety Gear	6
3.10 9 Front Body Mounting.....	67
4. MODIFICATIONS	7
4.1 Legal Modifications	7
4.2 Gray Areas and Questions	7
4.3 Replacement Parts/OEM Specifications.....	7
4.4 Special Required Equipment	7
4.5 Limited Production Parts.....	7
4.6 Updating/Back Dating	7
4.7 Non-Conforming Equipment.....	7
5. GENERAL VEHICLE SPECIFICATIONS	7
5.1 Ground Clearance.....	7
5.2 Weight.....	78
5.2.1 Ballast.....	8
5.3 Fasteners	8
6. APPEARANCE REQUIREMENTS	8
6.1 Body Specifications	8
6.2 Required Sponsor Decals	8
6.3 Optional Body Components.....	8
7. INTERIOR	89
7.1 Seat/Steering Wheel	9
7.2 Shifter Assembly	9
7.3 Pedals	9
7.4 Instrumentation.....	9
7.5 Interior Sheet Metal.....	9
7.6 Parking Brake	9
7.7 Dashboard.....	9

8. ELECTRICAL	9
8.1 Battery	9
8.2 Wiring	910
8.3 Lights	10
8.4 Ignition	10
8.5 Starter	10
9. HORSEPOWER/TORQUE/WEIGHT	10
9.1 Horsepower/Torque and Minimum Weight	10
9.1.1 Horsepower/Torque/Weight Table	10
9.1.2 Horsepower/Torque/Weight Documentation	10
9.2.1 Fuel Pressure	11
9.2.2 Timing	1112
10. ENGINE	12
10.1 Eligible Models	12
10.2 Engine Rebuilding	12
10.3 Rocker Arms Roller Rockers 1.7 ratio	12
10.4 Valve Springs	12
10.5 Compression Ratio	12
10.6 Harmonic Damper	12
10.7 Balancing	1213
10.8 Lubrication	13
10.9 Exhaust	13
10.10 Smog Equipment	13
10.11 Mounts	13
10.12 Valve Covers	13
10.13 Water Pump/Alternator/Accessory Pulleys/Belts/Brackets	13
10.14 Rev Limiter	1314
11. FUEL SYSTEM	14
11.1 Fuel Delivery System	14
11.2 Air Induction	14
11.3 Fuel Pump	14
11.4 Fuel Mixture Computer	14
11.5 Fuel Lines	14
11.6 Fuel	14
12. HEAT EXCHANGE	14
12.1 Radiator	14
12.1.1 Radiator Shielding	1415
12.1.2 Hoses / Filler	15
12.1.3 Fans/Thermostats	15
12.2 Oil Cooler	15
12.3 Catch Tanks-Oil	15
12.4 Fuel Cooling System	15
13. TRANSMISSION	15
13.1 Eligibility	15
13.2 Disallowed/Alternative Transmissions	15
13.3 Clutch/Flywheel	15

14. DIFFERENTIAL/AXLES	15
14.1 Differential/Gear Ratio	15
14.2 Rear Axles	1546
14.3 Drive Shaft	16
14.4 Traction Control	16
15. CHASSIS/SUSPENSION	16
15.1 Chassis- Repairs	16
15.2 Chassis-Strengthening	16
15.3 Suspension Components	16
15.4 Wheels and Tires	16
15.4.1 Wheels	16
15.4.2 Wheel Studs	16
15.4.3 Tires	16
16.1 Pads/Shoes	17
16.2 Brake Hoses	17
16.3 Master Cylinder/Associated Hardware	17
16.3.1 Fluid	17
16.3.2 Associated Hardware	17
16.4 Brake Calipers and Drums	17
16.5 Disk Brake Modifications/Cooling	17
16.6 Prohibited Brake Components	17
17. SUSPENSION/STEERING	17
17.1 Control Arms/Bushings	17
17.2 Spring Rates	17
17.3 Shocks	1748
17.4 Suspension Mounting Points	18
17.5 Steering Rack	18
18. FACTORY FIVE CONTACT INFORMATION	18
Appendix A	19
FFR Challenge Series Horsepower/Torque/Weight Table	19

1. INTRODUCTION

1.1 Intent

The intent of the Factory Five Racing Challenge Series is to provide National Auto Sport Association (NASA) members a truly affordable, fun, and competitive spec racing series in an interesting purpose built car. Good sportsmanship is valued more than finishing position. This means clean, well-executed passing is to be a trademark of the series. Punting another competitor, or leaning on them to gain a position will not be tolerated. Car to car contact including bump drafting can result in an investigation and possible sanctions. The following rules are not guidelines for this class, but an actual listing of allowed and required modifications. All cars and drivers must conform to *NASA's Club Codes and Regulations (CCR)*. Where different, the information in this publication supersedes the CCR and any preceding publication.

1.2 Acronyms Defined

CCR refers to the *NASA Club Codes and Regulations*

FFR refers to Factory Five Racing

NASA refers to the National Auto Sport Association, Inc.

NASCAR refers to the Nation Association of Stock Car Auto Racing, Inc.

2. ELIGIBLE MODELS

2.1 Definitions

Eligibility is applied in two ways. 1) The eligibility of the actual race-ready car. 2) The eligibility of the Ford Mustang (and/or parts, thereof) obtained for use in assembling the race-ready car.

2.1.1 Factory Five Racing Kit Car Eligibility

The term “eligible model” is used throughout this publication in context only. This is a kit-car or a “home-built” car. Therefore, a “finished car,” built according to the Factory Five instructions, these series rules, and other applicable NASA rules, is considered an “eligible model” for the series. This model shall be known as Factory Five Challenge Series Racer. (*FFR part #5003*)

2.1.2 Ford Mustang ‘Donor’ Car Eligibility

Parts from a “donor” car are required to assemble the finished race car. The term “eligible model,” found within this publication in the context of references to any parts or assemblies that is (or was) found on the donor car, should be considered a reference to the 1987 through 1993 Fox bodied Ford Mustang model with the Ford 5.0 liter (302 cubic inch) high-output 225 horsepower (factory rating) engine, unless otherwise specified.

3. SAFETY

3.1 Conformance to the *NASA Club Codes and Regulations (CCR)*

All cars and drivers must conform to NASA’s *Club Codes and Regulations (CCR)*. Where different, the information in this publication supersedes the CCR.

3.2 Cage/Rollover Protection

All cars must utilize the factory rollover protection system. The system may not be modified without written approval from NASA. In any case, all cars are required to maintain the rollover protection structure to the most current standards, unless otherwise specified in writing by NASA. Notation must be made in the car logbook indicating NASA approval of the modifications.

3.3 Drive Shaft Safety Loop

The installation of a safety loop to contain the drive shaft is required.

3.4 Scattershield

The installation of any SFI approved scattershield, SFI approved (specifically for manual transmissions) scattershield blanket or explosion-proof bell-housing is required.

3.5 Master Switch

The installation of an electrical master “cut-off” switch meeting CCR specifications is required.

3.6 Fuel Cell

The factory provided fuel cell must be maintained and must utilize a rollover valve (check valve) or have the filler neck removed and a fill plate accessible from inside the trunk installed on the tank to prevent leakage in the event the vehicle rolls over. Recommended rollover valve: Fuel Safe part number FV290A. Recommended fill plate: Fuel Safe part number SF6x10B. The fuel cell vent may be replaced with a larger vent to allow for faster fuel filling. The vent must contain a check valve to prevent leakage in case of a roll over.

3.7 Fuel Cell - Trunk Access

An opening in the trunk floor aluminum may be created to access the filler neck and other fuel cell components. The 3/4" tube below the trunk floor above the cell opening may be cut or repositioned to facilitate access. This opening can be no larger than 100 square inches. It is recommended but not required that this opening be covered with a hinged or removable aluminum cover to help reduce the effects of a fuel cell fire. Every effort should be made to minimize the size of this opening. All other trunk aluminum must be installed as intended.

3.8 7 Anti-intrusion protection

All cars are required to install anti-intrusion plates on at least the driver’s side. Passenger side anti-intrusion plates are allowed. Anti-intrusion plates shall be at least one eighth (1/8) inch thick steel or one eighth (1/8) inch thick aluminum and cover the outside part of the door bars. The plates may be welded in place or u-bolted to the door bars. If welded in place, each weld must be at least three inches long with a minimum of three welds on each of the top and bottom edges. If u-bolts are used, there must be at least two u-bolts installed on opposite edges of each plate.

3.9 8 Safety Gear

All drivers are required to utilize a closed-face helmet, with a certified shatter resistant face-field. This helmet must conform to all standards listed in the CCR. All drivers must utilize arm-restraints to help prevent injuries to the hands and arms in the event of a rollover. Drivers of vehicles that have window nets must still wear arm restraints.

3.10 9 Front Body Mounting

To help prevent intrusion of the body into the driver's compartment, the cowl area of the body (the area above and forward of the dash) must be through bolted to the two ¾" steel tubes on the chassis that extend forward from the dash hoop into the engine bay. Two 5/16 inch diameter bolts must be used on each side. Large washers should be used on both the body and chassis sides to prevent bolt heads from being pulled through.

4. MODIFICATIONS

4.1 Legal Modifications

Other than those items specifically allowed by these rules and any addendums, no other part or component that could affect performance may be added, modified, removed, or disabled. Addendums include any applicable official publications or parts lists from the NASA national office.

4.2 Gray Areas and Questions

If there are any 'questionable' or 'gray' area modifications, the competitor should contact the NASA office for clarification and written permission before competition.

4.3 Replacement Parts/OEM Specifications

Replacement parts must be original equipment manufacturer (OEM) or others of equivalent OEM specifications, unless otherwise specified in writing by Factory Five and/or NASA.

4.4 Special Required Equipment

Some equipment may be required to fulfill series sponsor requirements.

4.5 Limited Production Parts

Use of OEM parts, systems, and components that were only made for use in limited production models or prototypes is prohibited.

4.6 Updating/Back Dating

Parts or components may be updated/backdated using any legal parts. When updating or backdating, safety related components shall not be removed. Adding or moving the harness bar is specifically permitted to allow for proper harness installation.

4.7 Non-Conforming Equipment

Any equipment, which does not conform to the rules, must have prior approval. For considerations, approval must be made to NASA, in writing, 30 days prior to the date of competition. It is the intention of this class not to allow any modifications that would increase the cost of competition.

5. GENERAL VEHICLE SPECIFICATIONS

5.1 Ground Clearance

No part of the car, including the front air dam (spoiler), shall be lower than the lowest part of the wheel rims.

5.2 Weight

All vehicles must weigh at least 2400 lbs. Cars shall be weighed with the driver. Some cars may have higher minimum weights based on horsepower and torque. See table in Appendix A.

5.2.1 Ballast

Ballast is allowed; and if installed, it must be securely attached to the passenger side floor. Each ballast piece shall not be taller than three inches nor stacked higher than three inches. Each ballast piece must be made of solid material and weigh at least 2.2 kilograms (225.0 grams tolerance), five (5) pounds. Ballast must not serve any other function than to add weight to the car. A steel plate may be welded under the passenger side floor for ballast attachment.

5.3 Fasteners

Fasteners are unrestricted provided they serve the same function as originally intended and/or are used in a conventional manner.

6. APPEARANCE REQUIREMENTS

6.1 Body Specifications

Bodies must be OEM stock from FFR and must maintain stock contours. The main body shell may be cut into no more than two pieces to facilitate mounting and repair. The entire seam between the two body sections must lie between the leading and trailing edges of the door opening when viewed directly from above and the original mounts and fastener types must be retained. FFR may release, from time to time, addendums with optional body cuts.

6.2 Required Sponsor Decals

All decals required by the organizers and sponsors must be displayed in their appropriate positions. No decals from any company, organization, or manufacturer may be displayed that conflicts with any series sponsors. Factory Five is considered a sponsor and four Factory Five decals are required to be displayed on the car.

6.3 Optional Body Components

- a) A front air-dam (spoiler) may be used. *It must be the one provided by FFR or made of aluminum with the same dimensions and thickness as the one provided by FFR. The method of mounting is unrestricted.*
- b) Hood, trunk, and door fasteners may be replaced provided they securely mount each panel to the body in its intended position and serve no other purpose.
- c) Any mirrors may be used.
- d) An additional competition windscreen (FFR part # 12040) may be mounted on the passenger side and may be trimmed to match the body contour on that side. Full width windshields or wind screens are not permitted.
- e) A bumper may be added to the rear of the car only. The bumper should serve no other purpose than to minimize body damage to the rear of the car in the event of a collision, and may extend no more than 5 inches past the body at any point.
- f) The original “Quickjack” style bumpers may be removed from the front and rear.
- g) Front and rear splash panels may be removed but not modified.

7. INTERIOR

7.1 Seat/Steering Wheel

The steering wheel and seat may be replaced, providing that it meets with the applicable rules in the CCR. Removable steering wheels are allowed and any passenger seats are allowed.

7.2 Shifter Assembly

The shifter assembly and/or any components thereof, may be modified or may be replaced with any mechanical linkage shifter assembly and/or components, providing that the functionality remains only as originally intended. The transmission housing may be modified or swapped to accommodate different types and locations of shifter mechanisms as long as the modifications serve no other purpose.

7.3 Pedals

The pedal assembly including brake, clutch, and accelerator pedals may be modified or replaced with any pedal assembly or combination of assemblies provided that the functionality remains only as originally intended. No power assist, anti-lock or any other additional functions may be added. Alternate clutch, brake and throttle pedals are allowed including their mounting systems. The clutch release system must maintain cable actuation. The foot box area may be modified to install the pedal system.

7.4 Instrumentation

Any gauges may be used, provided that they do not violate any other applicable rules.

7.5 Interior Sheet Metal

All of the interior sheet metal panels must be installed in their intended locations or alternately may be replaced by aluminum or steel panels of equivalent or greater thickness. The interior sheet metal may be altered to fit a larger seat on the driver's side.

7.6 Parking Brake

The parking brake, its mechanisms, and its actuating components are optional.

7.7 Dashboard

The FFR OEM dashboard shall not be altered, except for as provided in these rules. Note: The "instrument cluster" (face) may be modified in order to install gauges and switches. Additionally, the dashboard may be altered to allow for knee/leg clearance.

8. ELECTRICAL

8.1 Battery

The battery must remain in the stock location on the passenger side of the lower trunk. The battery must be 12-volt and may not be modified in any way. The battery has a minimum weight of 25 lbs.

8.2 Alternator *moved to 10.13*

~~Alternators are unrestricted provided that they meet all other applicable rules. The alternator must be installed in the stock location and be OEM or direct OEM replacement. The alternator must be charging according to the manufacturer's specifications (for voltage and amperage, including while under load). Other than the main electrical master safety cut-out switch, any type of alternator cutoff switch is prohibited.~~

8.2 Wiring

Removal of wiring associated with components that may be legally removed, is permitted. The factory wiring harness may be replaced with an aftermarket wiring harness provided that the new harness functions identically to the OEM harness and in no way alters the signals between the sensors to the Engine Control Unit.

8.3 Lights

All vehicles must have a minimum of two functioning OEM rear brake light assemblies. All other OEM light assemblies must remain in place to maintain the stock external appearance, they need not function; and their wiring and bulbs may be removed. The OEM headlight assemblies may be replaced with covers that follow the original contour of the lights and are installed under the factory chrome trim rings.

8.4 Ignition

Any spark plugs and ignition wires may be used. All other ignition components and all internal distributor parts must be OEM stock and remain unaltered. Any initial timing is allowed but no re-curving of the distributor is permitted.

8.5 Starter

A stock OEM starter from an eligible model Mustang must be used.

9. HORSEPOWER/TORQUE/WEIGHT

9.1 Horsepower/Torque and Minimum Weight

It is required that every car have an initial dynamometer certification. This certification consists of two parts, a completed FFR Dyno Spec Sheet and Dyno Sheet Readout Graph. All pages must be signed and dated by the dynamometer operator performing the tests.

The FFR Dyno Spec Sheet includes instructions for performing the official dynamometer certification, which must be followed in order for the dyno certification to be valid. The Dyno Spec Sheet is available at www.NASAProRacing.com.

An annual dyno certification is not required but recommended. Re-certification is the responsibility of the owner after any change to the vehicle that could affect horsepower, torque, and weight. (e.g. legal engine modifications, timing, fuel pressure, other)

9.1.1 Horsepower/Torque/Weight Table

The Table referenced below will be used to determine the minimum weight for the car based on horsepower and torque. Minimum weight is measured immediately after qualifying and/or race, including driver.

See HP/T/W Table in Appendix A

9.1.2 Horsepower/Torque/Weight Documentation

Each competitor will submit the original Dyno Sheet and Spec Sheet to the Region Series Director and keep a copy of both sheets with their NASA Logbook. Current horsepower, torque, and weight numbers shall also be recorded inside the front cover of the Logbook to aid officials in completing tech inspection documentation. i.e. Most regions now require tech stickers on the car that include the horsepower, torque, and weight numbers.

9.2 Inspection and Testing

To help reduce the cost of competition and provide for simple and fair technical inspections, NASA shall use chassis dynamometer testing as the main means of engine inspection in the FFR Challenge Series.

NASA officials have the right to inspect anything in sight at any time the car is at the track. NASA officials shall have the right to request disassembly or any other procedure required to verify vehicle compliance with these rules including a dynamometer test.

The DynoJet brand is the required type of dyno for testing and inspection.

All dyno readings must be corrected to SAE J1349 Rev JUN90 (29.23 in/hg, 77F, zero humidity) and the dyno's smoothing function must be set to 5.

Altitude of the dyno shop must be recorded. **Dyno runs made at locations with elevation greater than 1,500 feet higher than the track will not count as being valid at that track.**

At the discretion of the NASA official, any car may be ordered to report for inspection on a chassis dynamometer at any time. If the result of the dyno test shows a car non-compliant: ~~with section 9.1.2 of these rules:~~

1. The competitor will be disqualified for the qualifying session or race for which the test was performed.
2. If it is a random test, the competitor will be excluded from competition until corrections are made.

In either case, the competitor must make corrections before further competition. This may include de-tuning the engine to produce horsepower and torque numbers for a given weight or by adding additional weight to match the horsepower and torque numbers as determined by the ~~section 9.1.2 table~~ *in Appendix A*.

Fuel Pressure and Timing checks may be used as an alternative to Dyno Testing. Readings will be compared to the Dyno Spec Sheet to determine compliance.

9.2.1 Fuel Pressure

The fuel pressure on all cars shall be noted on the Dyno Sheet. A +/- 2psi range is allowed.

All fuel pressure readings must be taken with the engine running and the vacuum line on the pressure regulator disconnected.

If fuel pressure is tested in impound and the reading from the first gauge is found to be outside of the range listed on the competitor's Dyno Sheet, a second fuel pressure gauge may be used if available. In this case the average of readings from the two gauges shall be used to determine the fuel pressure readings.

Any car with a fuel pressure reading that does not meet the above specifications in impound shall be disqualified.

9.2.2 Timing

A +/- 1 degree range is allowed.

If the initial timing is tested and is found to be outside the allowable range, a second light may be used if available. The reading obtained with the second light shall be final.

Timing will be checked with the "spout" removed. The "spout" shall be in place during all competitions.

10. ENGINE

10.1 Eligible Models

Any 5.0 liter 1987-1993 Mustang (302ci Ford) V8 production engine, in OEM configuration is legal, providing that it meets with all other applicable rules. Cobra model engines and engine components are prohibited.

10.2 Engine Rebuilding

Rebuilding a stock engine is permissible with a maximum overbore of 0.060 (inches). Engine gaskets are unrestricted providing they do not increase compression ratio beyond the maximum value allowed.

Replacement pistons, connecting rods, wrist pins, and piston rings must match OEM parts dimensionally (except to match a legal bore size) and may weigh no less than the parts they replace. The unmodified OEM stock camshaft or the direct replacement Melling part #SYB-51 must be used.

All other factory components or direct replacement parts (matching the original OEM parts exactly) must be maintained. Titanium parts are not permitted. Internal engine coatings are not permitted. Grinding, polishing or removal of any material other than as required to mate surfaces in the cylinder heads or intake manifold ports is not permitted. Stock OEM valve seat specifications must be maintained.

10.3 ~~Rocker Arms~~ ~~Roller Rockers~~ ~~1.7 ratio~~

The factory OEM rocker arms may be replaced with *any roller rocker arm with a ratio up to 1.7.. The owner must declare the brand, part number, and ratio on the Dyno Spec Sheet.* ~~Ford part# M6564 A50 or Crane Cams part# 44746 16. If using these rocker arms the complete set of 16 must be used.~~

10.4 Valve Springs

Any single coil steel valve spring may be used.

10.5 Compression Ratio

The stock compression ratio must be maintained +/- 0.2 mechanical compression units (measured).

10.6 Harmonic Damper

Any harmonic damper may be used as long as it weighs at least 9 lbs. and its outside diameter is 6" or greater.

10.7 Balancing

No balancing is permitted.

10.8 Lubrication

Oil Filters, adapters, and lines may be replaced or added. Any oil pan and windage tray combination may be used, provided it serves no other purpose (such as stiffening the block, for example) other than oil control and it conforms to all other applicable rules. A pressure accumulator such as an “Accusump ®” may be used. Any lines that pass through the passenger compartment must be metal or metal braided. All lines must be securely fastened and safely routed. Dry sump lubrication systems are prohibited. Any oil or lubricants are allowed, except as a fuel additive.

10.9 Exhaust

All cars may use any exhaust headers provided that they mate with the Factory Five “J- pipe” and do not change the location or function of this pipe. No crossover tubes or balance tubes are allowed. Additionally the Factory Five provided side pipes must be installed in the standard location as a working part of the exhaust system. Mufflers may be required to meet sound regulations and are unrestricted, providing that they serve no other purpose than to quiet the exhaust. The entire exhaust system may be coated or wrapped to retain heat. Additional mounting points may be used to support the exhaust as long as that is their only function. (e.g. j- pipe hangars)

10.10 Smog Equipment

Any smog equipment may be removed, including the catalytic converter(s). Any smog equipment not removed must either be disabled or left to function as originally intended by the manufacturer. All disconnected ports and holes must be sealed.

10.11 Mounts

Engine and transmission mounts must be OEM stock or “Energy Suspension” part # 4.1122G (engine), 4.1104G (transmission).

10.12 Valve Covers

Any valve cover may be used as long as it functions exactly as the OEM stock covers, serves no other function, and fits under the unmodified OEM intake manifold.

10.13 Water Pump/*Alternator*/Accessory Pulleys/Belts/Brackets *Moved Alternator from 8.2*

The OEM (or direct replacement) water pump must be used. *Alternators are unrestricted provided that they meet all other applicable rules. Other than the main electrical master safety cut-out switch, any type of alternator cutoff switch is prohibited.* Accessory drive and driven pulleys may be replaced with alternate pulleys designed for a 6-rib serpentine belt system. A-6-rib serpentine drive belt of any length must be used.

The smog pump and power steering pump may be removed. If the smog pump is removed, all associated plumbing must be removed and disconnected holes plugged.

Any alternator bracket may be used as long as it mounts the centerline of the alternator pulley at or above the top of the engine block. Any power steering bracket may be used as long as it mounts the centerline of the power steering pulley at or above the centerline of the water pump pulley.

10.14 Rev Limiter

A rev limiter may be installed so long as it does not interfere with the ECU management of the engine including the ECU's built-in limit for engine RPM.

11. FUEL SYSTEM

11.1 Fuel Delivery System

The factory fuel system, including 19 lb. injectors must be used. The OEM fuel pressure regulator may be replaced with an adjustable fuel pressure regulator. Only one pressure regulator per car is allowed. Any adjustable regulator may be used that fits on the factory OEM mount and has a single screw adjustment and a vacuum port. There must be a *stock type Schrader valve for testing* fuel pressure. ~~port available for testing fuel pressure.~~ It must be *installed in the high pressure side of the system.* ~~located near the fuel rails in the pressure line.~~

11.2 Air Induction

The stock air induction tube and stock unmodified mass air meter with screen must be retained with no additional tubing used. Heat shielding is permitted so long as it does not act to direct the flow of air. The air filter element, as supplied with the kit or an exact equivalent, must be used and must draw air entirely from inside the engine compartment. The factory intake-manifold, including throttle body and spacer, as well as heads, camshaft, rocker arms etc. must remain stock. The stock EGR spacer must be maintained, but the EGR need not be operational.

11.3 Fuel Pump

An OEM fuel pump or FFR provided fuel pump is required and must be mounted in the OEM specified location inside the fuel cell. No additional fuel pumps may be used. Fuel filters, lines, and hoses are unrestricted except that the maximum inside diameter (ID) of all fuel lines/hoses is 1/2 inch. The return line must flow freely from the regulator to the fuel cell and not affect fuel pressure.

11.4 Fuel Mixture Computer

The Engine Control Unit must be one of the following from a 1989 through 1993 Mass Air Sensor equipped engine: A9L, A3M, 3M1, S0Z, D3D1, A9M, A9P, C3W, C3W1, A9T, A9S, or 8LD. Modifications to the computer (including any reprogramming or add on modules) or fuel injection system are prohibited, unless otherwise specified by these rules. Note: The fuels/ignition computer may be exchanged with any other competitor's computer unit, at the discretion of the Chief Scrutineer or the Race Director.

11.5 Fuel Lines

Any fuel lines or hoses that pass through the cockpit compartment must be metal or metal braided as well as securely fastened and safely routed.

11.6 Fuel

Any unleaded gasoline is allowed. Fuel additives are not permitted.

12. HEAT EXCHANGE

12.1 Radiator

Any radiator may be used provided it fits in the stock location. A shroud may be added to direct the air across the radiator.

12.1.1 Radiator Shielding

A screen may be mounted in front of the radiator and oil cooler to prevent damage to these components. The screen must allow air to flow through freely and cannot be used for aerodynamic purposes.

12.1.2 Hoses / Filler

Stainless steel hoses are allowed as well as any in-line "T" filler neck.

12.1.3 Fans/Thermostats

Cooling fans and thermostats are unrestricted.

12.2 Oil Cooler

Oil coolers, including power steering, transmission, rear end, and engine oil may be replaced or added. All lines must be securely fastened and safely routed.

12.3 Catch Tanks-Oil

All engine oil breathers must vent to a catch tank of at least one U.S. quart capacity. Catch tanks shall not be mounted in the passenger compartment.

12.4 Fuel Cooling System

Fuel cooling systems, of any kind, are prohibited.

13. TRANSMISSION

13.1 Eligibility

An OEM T-5 transmission that was originally offered in a model year 1987-1993 V8 Mustang must be used, unless otherwise specified by these rules. Standard ratios must be maintained. Alternatively, a Tremec (part#3550 or TKO500) or T5Z (part #M-7003- Z) may be used, but only with the following ratios: 1st gear 3.27, 2nd gear 1.98 or 1.97, 3rd gear 1.34, 4th gear 1.00, 5th gear .68. *or a Tremec T5Z (part #M-7003-Z) may be used.* Transmissions must be unmodified and gears may not be shaved, polished, trimmed, or otherwise changed.

13.2 Disallowed/Alternative Transmissions

Transmissions shall not be modified and no alteration to OEM stock transmission ratios is permitted. Automatic and semi-automatic transmissions are not allowed. Cars originally equipped with an automatic transmission may convert to a legal manual transmission.

13.3 Clutch/Flywheel

Any single disc clutch and steel pressure plate of OEM stock diameter may be used provided that it bolts directly to an unmodified OEM stock flywheel.

14. DIFFERENTIAL/AXLES

14.1 Differential/Gear Ratio

The OEM stock 8.8 differential from the eligible model must be maintained. Those using C-clip eliminators and 31 spline axles may use the differential from a Ford truck as long as it is the same Ford "Trac-Loc" differential. The use of Ford clutches and increasing the preload on the limited slip is permitted provided that no machining is done. A 2.73:1 gear ratio must be used in all cars. No modifications are permitted including shaving, polishing, or trimming.

14.2 Rear Axles

Any commercially available replacement type steel or alloy steel axles may be used. Full floater axles are prohibited. "C-clip" eliminators are allowed, however competitors should check with the "C-clip" eliminator manufacturer as to the ability of their "C-clip" eliminator to withstand the side loads associated with road racing. **Notice: Many of the "C-clip" eliminators are designed for street or drag strip use only and are not necessarily adequate for use in road racing.** A catch can to catch overflow from the rear axle is permitted.

Negative camber measured on either rear wheel must not exceed 0.5 degrees.

14.3 Drive Shaft

The drive shaft must be made of steel.

14.4 Traction Control

Traction or launch control of any type is not permitted.

15. CHASSIS/SUSPENSION

15.1 Chassis- Repairs

All chassis and structure repair must be done as close as possible to a FFR factory original configuration.

15.2 Chassis-Strengthening

The frame must be maintained as stock and made of mild steel. Alterations made to the roll cage must function to enhance safety and must be approved by NASA. Alterations made solely for the purpose of stiffening the chassis will not be approved.

15.3 Suspension Components

The rear suspension must utilize either the eligible factory Mustang parts or the FFR kit parts. Any FFR supplied rear suspension part for the series cars may be replaced with the corresponding OEM part, at the option of the car owner. Under no circumstances shall any parts for the rear suspension be used other than the OEM parts, and/or the FFR supplied parts, unless otherwise specified by these rules. Travel limiters in the form of rubber bump stops and/or cables may be added to or removed from the suspension, provided that they serve no other purpose than limiting total suspension travel in compression or droop. Spindles may not be bent.

15.4 Wheels and Tires

15.4.1 Wheels

Rims must be 17 inch in diameter with a maximum width of 9 inches and weigh no less than 20 pounds each.

15.4.2 Wheel Studs

Wheel studs and lug nuts are unrestricted. However, they must be made of steel and be no smaller in size than the OEM part.

15.4.3 Tires

The spec tire model is a 255/40/17 Toyo Proxes RA-1. Shaving and/or grooving of the tire is permitted.

16. BRAKING SYSTEM

16.1 Pads/Shoes

Brake pads and shoes are unrestricted. Brake lining material is unrestricted.

16.2 Brake Hoses

Rubber brake lines/hoses may be replaced with suitable metal braided lines. Brake lines/hoses may be relocated and may be given additional protection providing that it serves no other purpose than to protect the brake line. All brake lines/hoses must be securely fastened and safely routed. Brake fittings, adapters, and connectors are unrestricted.

16.3 Master Cylinder/Associated Hardware

Any non-power assisted brake master cylinder or multiple cylinder assembly is permitted.

16.3.1 Fluid

Brake fluid is unrestricted, provided that it only serves its intended use, as stated by the manufacturer.

16.3.2 Associated Hardware

An adjustable brake-proportioning valve (one) may be used. The original proportioning (or biasing) valve shall not be modified, but may be removed. However, if it is removed, it must be removed in its entirety.

16.4 Brake Calipers and Drums

Unless otherwise specified, stock Mustang 5.0 (1987-1993) front disc brakes and rear drums must be used. Alternatively, the rear drums may be replaced by four or five lug disc brakes with metal rotors outside diameter of no greater than 10.5 inches and a single cast iron single piston caliper per side. A common source of rear disc brakes is found on any 1987-88 Ford Thunderbird Turbo coupe or 1994 and later GT model Mustang, and the entire rear axle housing can be used from either of these vehicles. The axle length may be changed to accommodate the brakes; however the rear track width shall not exceed 58.5 inches as measured from the center of the rear tires. Front rotors may be replaced with 5 lug units that are otherwise identical.

16.5 Disk Brake Modifications/Cooling

Disk brake backing plates may be replaced, removed, or modified. Air ducts may be fitted to the brakes providing that no holes are made in the body.

16.6 Prohibited Brake Components

Antilock braking systems (ABS) and power brake systems are prohibited.

17. SUSPENSION/STEERING

17.1 Control Arms/Bushings

Stock FFR control arms and bushings (polyurethane) must be used.

17.2 Spring Rates

Front and rear coil-over spring rates are unrestricted. The source of these replacement springs is unrestricted.

17.3 Shocks

Shocks must be used as specified by Factory Five and cannot not be re-valved or modified in any way. The spec front shock is Koni #30-1720 (FFR#14622). The spec rear shock is Koni #30-1721 (FFR#14623). Alternatively, the Bilstein 274SR rear shock may be used on the rear until ~~12/31/2009~~ **12/31/2012**. **NOTE - The use of Bilstein 273SR front shocks is strictly prohibited.**

17.4 Suspension Mounting Points

Suspension pick up points (mounting points) shall not be altered in any way unless updating an older car to newer specifications. In the case of an update, the new pickup points must meet with existing factory specifications exactly (within specified tolerance). In a case where no factory tolerance is listed, the mounting point must be within +/- 1.0% of the listed (or common, if not listed) measurement.

17.5 Steering Rack

The steering rack from any 1987-1998 mustang may be used along with the power steering pump from any 1987-1993 Mustang. The steering rack may also be replaced with a manual unit providing it is a direct bolt in and there is no change in the steering geometry. The steering rack may be mounted in either location provided for in the FFR assembly instructions. Inline pressure reduction valves are permitted and the pressure may be adjusted on any allowable power steering pump.

18. FACTORY FIVE CONTACT INFORMATION

Factory Five Racing, Inc.
9 Tow Road, Wareham, MA 02571
(508) 291-3443

General Information (508) 291-3443 info@factoryfive.com

Technical Support <mailto:tech@factoryfive.com>

Appendix A

FFR Challenge Series Horsepower/Torque/Weight Table

HP/T	<=285	286	287	288	289	290	291	292	293	294	295	296	297	298	299	300	301	302
<=220	2400	2405	2410	2414	2419	2424	2429	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481
221	2405	2410	2414	2419	2424	2429	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486
222	2410	2414	2419	2424	2429	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490
223	2414	2419	2424	2429	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495
224	2419	2424	2429	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500
225	2424	2429	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505
226	2429	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509
227	2433	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514
228	2438	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519
229	2443	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524
230	2448	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528
231	2452	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528	2533
232	2457	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528	2533	2538
233	2462	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528	2533	2538	2543
234	2467	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528	2533	2538	2543	2547
235	2471	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528	2533	2538	2543	2547	2552
236	2476	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528	2533	2538	2543	2547	2552	2557
237	2481	2486	2490	2495	2500	2505	2509	2514	2519	2524	2528	2533	2538	2543	2547	2552	2557	2562